

4K Mini NVR

4/8-CH Video Input • Up to 10TB Storage • Ultra-mini Size • Decode up to 1-CH 4K UHD & 4-CH 1080P • ANR



| MODEL | | TA-V11004-UK | TA-V11008-UK |
|----------------------|-----------------------|---|---|
| VIDEO INPUT | Network Video Input | 4-CH | 8-CH |
| | Incoming Bandwidth | 40Mbps | 80Mbps |
| | Outgoing Bandwidth | 40Mbps | 80Mbps |
| VIDEO OUTPUT | HDMI Output | 1-CH, Resolution: 3840x2160/30Hz, 1920x1080/60Hz, 1920x1080/50Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz HDMI Supports Audio Output | |
| | Dual Stream | Support | |
| | Recording Resolution | 8MP/6MP/5MP/4MP/3MP/1080P/UXGA/720P/D1/VGA/CIF/QCIF | |
| | Synchronous Playback | 1*(30fps @8MP), 1*(30fps @6MP), 1*(30fps @5MP), 2*(30fps @4MP), 2*(30fps @3MP), 4*(30fps @1080P), 4*(30fps @720P) | 1*(30fps @8MP), 1*(30fps @6MP), 1*(30fps @5MP), 2*(30fps @4MP), 2*(30fps @3MP), 4*(30fps @1080P), 8*(30fps @720P) |
| COMPRESSION | Video Compression | H.265+/H.265(HEVC)/H.264+/H.264 | |
| | Audio Compression | G.711/AAC/G.722/G.726 | |
| | Sample Rate | 8KHz/16KHz | |
| | Synchronous Recording | 4*5MP | 8*5MP |
| STORAGE | SATA | 1*SATA HDD (3.5") | |
| | Capacity | Up to 10TB capacity for each HDD | |
| RECORDING MANAGEMENT | Recording Type | Continuous, Event (Motion Detection, Alarm, VCA, Smart Analysis) | |
| | Snapshot Type | N/A | |
| | Playback Type | General Playback, Event Playback, Tag Playback, Split Playback, Picture Playback | |

| | | |
|--------------------|--------------------|---|
| BACKUP | Backup | Video Backup, Image Backup |
| | Protocol | IPv4/IPv6, TCP, UDP, RTP, RTSP, RTCP, HTTP, HTTPS, DNS, DDNS, DHCP, NTP, SNTP, SMTP, SNMP, UPnP, NFS |
| EXTERNAL INTERFACE | Network Interface | 1*RJ45 10/100Mbps |
| | USB Interface | 2*USB 2.0 |
| GENERAL | Compatibility | ONVIF, API |
| | Advanced Function | ANR |
| | ANPR | N/A |
| | Video Analysis | Region Entrance, Region Exiting, Advanced Motion Detection, Tamper Detection, Line Crossing, Loitering, Human Detection, People Counting, Object Left, Object Removed |
| | Keyboard Control | Supported for tAbysz Keyboard |
| | Power Supply | DC 12V 2A |
| | Consumption | ≤2.3W(Without HDD) |
| | Working Conditions | Temperature: -10°C~55°C/Humidity: 10%~90% |
| | Dimensions | 220mm(W)X200mm(D)X43.6mm(H) |
| | Weight | 0.19Kg |
| Warranty | 3/5 Years | |

Available In:



Structure Diagram:

