

4K Mini PoE NVR

4/8-CH Video Input • Up to 8TB Storage • Ultra-mini Size
• Decode up to 1-CH 4K UHD & 4-CH 1080P • ANR



MODEL		TA-V11004-UPK	TA-V11008-UPK
VIDEO INPUT	Network Video Input	4-CH	8-CH
	Incoming Bandwidth	40Mbps	80Mbps
	Outgoing Bandwidth	40Mbps	80Mbps
VIDEO OUTPUT	HDMI Output	1-CH, Resolution: 3840x2160/30Hz, 1920x1080/60Hz, 1920x1080/50Hz, 1280x1024/60H, 1280x720/60Hz, 1024x768/60Hz; HDMI Supports Audio Output	
	Dual Stream	Support	
	Recording Resolution	8MP/6MP/5MP/4MP/3MP/1080P/UXGA/720P/D1/VGA/CIF/QCIF	
	Synchronous Playback	1*(30fps @8MP), 1*(30fps @6MP), 1*(30fps @5MP), 2*(30fps @4MP), 2*(30fps @3MP), 4*(30fps @1080P), 4*(30fps @720P)	1*(30fps @8MP), 1*(30fps @6MP), 1*(30fps @5MP), 2*(30fps @4MP), 2*(30fps @3MP), 4*(30fps@1080P), 8*(30fps @720P)
COMPRESSION	Video Compression	H.265+/H.265(HEVC)/H.264+/H.264	
	Audio Compression	G.711/AAC/G.722/G.726	
	Sample Rate	8KHz/16KHz	
	Synchronous Recording	4*5MP	8*5MP
STORAGE	SATA	1*SATA HDD(3.5")	
	Capacity	Up to 8TB capacity for each HDD	
RECORDING MANAGEMENT	Recording Type	Continuous, Event (Motion Detection, Alarm, VCA, Smart Analysis)	
	Snapshot Type	N/A	
	Playback Type	General Playback, Event Playback, Tag Playback, Split Playback, Picture Playback	

BACKUP	Backup	Video Backup, Image Backup
NETWORK	Protocol	IPv4/IPv6, TCP, UDP, RTP, RTSP, RTCP, HTTP, HTTPS, DNS, DDNS, DHCP, NTP, SNTP, SMTP, SNMP, UPnP, NFS
EXTERNAL INTERFACE	Network Interface	1*RJ45 10/100Mbps
	USB Interface	2*USB 2.0
POE INTERFACE	Interface	4*RJ45 10/100Mbps
	Power Output	≤40W
	Supported Standard	IEEE 802.3af/at
GENERAL	Compatibility	ONVIF, API
	Advanced Function	ANR
	ANPR	N/A
	Video Analysis	Region Entrance, Region Exiting, Advanced Motion Detection, Tamper Detection, Line Crossing, Loitering, Human Detection, People Counting, Object Left, Object Removed
	Keyboard Control	Supported for tÄbysz Keyboard
	Power Supply	DC 48V 1.3A
	Consumption	≤3.5W(Without HDD, without enabling PoE)
	Working Conditions	Temperature: -10°C~55°C/Humidity: 10%~90%
	Dimensions	220mm(W)X200mm(D)X43.6mm(H)
	Weight	0.2Kg
Warranty	3/5 Years	

Available In:



Structure Diagram:

